

SaniLIGHT®

GERMICIDAL ULTRAVIOLET IRRADIATORS

Features:

- Constructed of corrosion-resistant Stainless Steel
- Fixtures utilize 1 or 2 **STER-L-RAY®** UV-C Germicidal Lamps to disinfect air and exposed surfaces
- Available with Instant Start (Standard Output), High Output (HO), or Cold Cathode (CC) UV-C Lamps
- Virtually all microorganisms are susceptible to SaniLIGHT® germicidal ultraviolet disinfection
- Very effective due to the long, unobstructed path of ultraviolet rays
- Continuous disinfection without special attention and low maintenance
- For ceiling or wall mount in UNOCCUPIED spaces



Model D24-1CC



Model D24-2S

SPECIFICATIONS—SaniLIGHT® Instant Start Models

Model	Lamp (Quantity)	Power Consumption ①	Total Ultraviolet Output ②	Dimensions (Inches)			Rated Lamp Life (Hours)
				Length	Width	Height	
D12-1S	05-1500-R (1)	12.0 Watts	3.1 Watts	13-1/4"	5"	3-3/4"	10,000
D18-1S	05-1340-R (1)	22.0 Watts	5.8 Watts	19-1/4"	5"	3-3/4"	10,000
D24-1S	05-1348-R (1)	30.7 Watts	8.5 Watts	25-1/4"	5"	3-3/4"	10,000
D30-1S	05-1352-R (1)	38.4 Watts	11.2 Watts	31-1/4"	5"	3-3/4"	10,000
D36-1S	05-1343-R (1)	42.9 Watts	13.8 Watts	37-1/4"	5"	3-3/4"	10,000
D48-1S	05-1334-R (1)	66.0 Watts	19.3 Watts	49-1/4"	5"	3-3/4"	10,000
D64-1S	05-1338A-R (1)	94.0 Watts	25.0 Watts	65-1/4"	5"	3-3/4"	10,000
D12-2S	05-1500-R (2)	24.0 Watts	6.2 Watts	13-1/4"	5-5/8"	3-3/4"	10,000
D18-2S	05-1340-R (2)	44.0 Watts	11.6 Watts	19-1/4"	5-5/8"	3-3/4"	10,000
D24-2S	05-1348-R (2)	61.4 Watts	17.0 Watts	25-1/4"	5-5/8"	3-3/4"	10,000
D30-2S	05-1352-R (2)	76.8 Watts	22.4 Watts	31-1/4"	5-5/8"	3-3/4"	10,000
D36-2S	05-1343-R (2)	85.8 Watts	27.6 Watts	37-1/4"	5-5/8"	3-3/4"	10,000
D48-2S	05-1334-R (2)	132.0 Watts	38.6 Watts	49-1/4"	5-5/8"	3-3/4"	10,000
D64-2S	05-1338A-R (2)	188.0 Watts	50.0 Watts	65-1/4"	5-5/8"	3-3/4"	10,000

① Total power consumption including ballast loss.

② Ultraviolet Output at 254 nanometers at 100 hours and 80 degrees F (approximate).



375 Marcus Boulevard, Hauppauge, NY 11788
 (631) 273-0500 • Fax: (631) 273-0771 • Email: Sales@AtlanticUV.com
 Shop: AtlanticUltraviolet.com • Learn More: Ultraviolet.com
 Document Number 98-1868 • May 2023 • ©2023 Atlantic Ultraviolet Corporation®



SPECIFICATIONS—SaniLIGHT® Cold Cathode Models

Model	Lamp (Quantity)	Power Consumption ①	Total Ultraviolet Output ②	Dimensions (Inches)			Rated Lamp Life (Hours)
				Length	Width	Height	
D12-1CC	05-0052A (1)	18.8 Watts	1.4 Watts	13-1/4"	5"	3-3/4"	20,000
D18-1CC	05-0040-R (1)	26.3 Watts	3.2 Watts	19-1/4"	5"	3-3/4"	20,000
D24-1CC	05-1118-R (1)	28.8 Watts	5.0 Watts	25-1/4"	5"	3-3/4"	20,000
D36-1CC	05-0044-R (1)	35.0 Watts	8.5 Watts	37-1/4"	5"	3-3/4"	20,000
D48-1CC	05-0042-R (1)	42.5 Watts	11.2 Watts	49-1/4"	5"	3-3/4"	20,000
D18-2CC	05-0040-R (2)	52.6 Watts	6.4 Watts	19-1/4"	5-5/8"	3-3/4"	20,000
D24-2CC	05-1118-R (2)	57.6 Watts	10.0 Watts	25-1/4"	5-5/8"	3-3/4"	20,000
D36-2CC	05-0044-R (2)	70.0 Watts	17.0 Watts	37-1/4"	5-5/8"	3-3/4"	20,000
D48-2CC	05-0042-R (2)	85.0 Watts	22.4 Watts	49-1/4"	5-5/8"	3-3/4"	20,000

① Total power consumption including ballast loss.

② Ultraviolet Output at 254 nanometers at 100 hours and 80 degrees F (approximate).

SPECIFICATIONS—SaniLIGHT® High Output Models

Model	Lamp (Quantity)	Power Consumption ①	Total Ultraviolet Output ②	Dimensions (Inches)			Rated Lamp Life (Hours)
				Length	Width	Height	
DHO18-1S	05-0687 (1)	58.0 Watts	11.5 Watts	19-1/4"	5"	3-3/4"	13,000
DHO24-1S	05-0686 (1)	73.7 Watts	17.0 Watts	25-1/4"	5"	3-3/4"	13,000
DHO30-1S	05-0685 (1)	92.2 Watts	23.0 Watts	31-1/4"	5"	3-3/4"	13,000
DHO36-1S	05-1060-R (1)	108.0 Watts	28.0 Watts	37-1/4"	5"	3-3/4"	13,000
DHO48-1S	05-0576 (1)	158.4 Watts	40.0 Watts	49-1/4"	5"	3-3/4"	13,000
DHO64-1S	05-0690 (1)	193.0 Watts	54.0 Watts	65-1/4"	5"	3-3/4"	13,000
DHO18-2S	05-0687 (2)	116.0 Watts	23.0 Watts	19-1/4"	5-5/8"	3-3/4"	13,000
DHO24-2S	05-0686 (2)	147.4 Watts	34.0 Watts	25-1/4"	5-5/8"	3-3/4"	13,000
DHO30-2S	05-0685 (2)	184.3 Watts	46.0 Watts	31-1/4"	5-5/8"	3-3/4"	13,000
DHO36-2S	05-1060-R (2)	216.0 Watts	56.0 Watts	37-1/4"	5-5/8"	3-3/4"	13,000
DHO48-2S	05-0576 (2)	316.8 Watts	80.0 Watts	49-1/4"	5-5/8"	3-3/4"	13,000
DHO64-2S	05-0690 (2)	386.0 Watts	108.0 Watts	65-1/4"	5-5/8"	3-3/4"	13,000

① Total power consumption including ballast loss.

② Ultraviolet Output at 254 nanometers at 100 hours and 80 degrees F (approximate).

Notes:

- 120 Volts 50/60 Hz and 230 Volts 50/60 Hz models are standard. Specify when ordering.
- Fixtures are available in various voltages. Consult factory with specific power requirements.
- Models with other lamp quantities and configurations available. Consult factory with specific requirements



375 Marcus Boulevard, Hauppauge, NY 11788
 (631) 273-0500 • Fax: (631) 273-0771 • Email: Sales@AtlanticUV.com
 Shop: AtlanticUltraviolet.com • Learn More: Ultraviolet.com
 Document Number 98-1868 • May 2023 • ©2023 Atlantic Ultraviolet Corporation®

