

# Ultraviolet Water Purifier Comparison Chart

## FEATURES

[S] - Standard • [O] - Optional • [X] - Yes

**Bio-Logic®**  
Pure Water Pack™  
1.5 GPM



**MINIPURE®**  
1 to 9 GPM




**MIGHTY★PURE®**  
3 to 20 GPM



**SANITRON®**  
3 to 20 GPM



**SANITRON®**  
40 to 416 GPM



**MEGATRON®**  
90 to 450 GPM



Stainless Steel Construction	S	S	S	S	S	S
<b>STER-L-RAY®</b> Germicidal Ultraviolet Lamp with 10,000 Hours Rated Effective Life	S	S	S	S	S	S
Quick Lamp Change with the <b>EASY-OFF™</b> Retainer Cap	S	S	S	S	S	S
<b>CRYSTAL CLEAR™</b> Quartz Sleeve	S	S	S	S	S	S
Lamp Out Indicator Light(s)	S	S	-	-	-	S
Sight Port to View Lamp Operation	-	-	S	S	S	S
Drain Fitting	-	-	S	S	S	S
Patented Dual Action Wiper Mechanism - Manual	-	-	-	S	S	S
Patented Dual Action Wiper Mechanism - Automatic	-	-	-	-	-	O
Head(s) that can be removed or rotated	S	-	-	S	S	S
Sediment and Carbon Filter	S	-	-	-	-	-
<b>Promate™</b> Mounting Kit / Bracket	S	O	O	O	O ①	-
<b>GUARDIAN™</b> Ultraviolet Monitor	-	-	O	O	O	S
<b>SENTRY™</b> Safety Sensor	O	O	O	O	O	-
<b>Promate™</b> Audio Alarm	S	S	O	O	O	-
<b>Promate™</b> Solenoid Valve	-	O	O	O	O	-
<b>SureFLO™</b> Flow Control Valve	-	O	O	O	O	-
<b>Promate™</b> Elapsed Time Indicator	O	O	O	O	O	S
<b>Promate™</b> Time Delay Mechanism	-	O	O	O	O	-
Residential Use	X	X	X	X	X	-
Commercial Use	-	-	X	X	X	X
CE Certified Models ②	-	-	X	X	X	-

NOTE: This list depicts options for 120v 50/60Hz operation. Consult factory for options with other power requirements.

① **SANITRON®** Model S10,000 & larger come equipped with mounting rack.

② **MIGHTY★PURE®** MP36C and **SANITRON®** S37C, S2400C, S5000C, S10,000C, S15,000C and S20,000C are available as CE Certified